



Sonar Safety Systems Inc.
Fleet Safety Technology Provider since 1993.

Hindsight 20-20® Rear View Camera Systems

CS-712 and CSW-712

CS-712



Offers up to 4 Video Inputs
Viewing Angel: Up 45°, Down 65°, Left and Right 65°
Operating Temperature: From -20° up to 65° Celsius
Power Source: 12v to 32v DC
Contrast 400:1
7" Color TFT LCD monitor
Audio Output 1000mw
Earphone Jack
Wireless Remote Control
Speaker Size 2.4 x 1.5 cm
Connection Terminals

1. A/V Out Put for DVD
2. A/V and Power Supply Conversion Cable Inputs
3. Camera Connectors

Resolution: 480 x 234 (RGB)
Brightness: 350 cd/m²
Comes with :
All cables and connectors, mounting hardware for the monitor and camera, remote controller, batteries, screws, and operating instructions.

CSW-712 Wireless



Frequency range: 2400-2483 MHZ
Maximum distance from camera 238M
Reception Capacity: -80dB
Automatic Back Lit Selection Buttons
Multiple Video Formats
4 Wireless Inputs
1 DVD Output
Auto Switch from Back, Left or Right side cameras
Viewing Angel: Up 45°, Down 65°, Left and Right 65°
Operating Temperature: From -20° up to 65° Celsius
Power Source: 12v to 32v DC
Contrast 400:1
7" Color TFT LCD monitor
Audio Output 1000mw
Speaker Size 2.4 x 1.5 cm
Connection Terminals
Resolution: 480 x 234 (RGB)
Brightness: 350 cd/m²
Comes with :
All cables and connectors, mounting hardware for the monitor and camera, remote controller, batteries, screws, and operating instructions.

Side view and additional rear view cameras are available for both systems as well as "Bullet" Style Cameras
Installation Diagrams on the next page.